


PORTABLE SUMERSIBLE PUMP এর পূর্ণাঙ্গ স্পেসিফিকেশন

Ser	Particulars	Description																																										
1.	Name of the equipment	Portable Submersible Pump																																										
2.	Quantity	01 in no																																										
3.	Purpose	Flooding/ De-flooding																																										
4.	Type	Marine																																										
5.	Model	To be mentioned																																										
6.	Standard	-																																										
7.	Technical data	<table border="1"> <tr> <td>a.</td> <td>Capacity</td> <td>35-45 Ton per hour</td> </tr> <tr> <td>b.</td> <td>Speed</td> <td>2700-3500 RPM</td> </tr> <tr> <td>c.</td> <td>Discharge Position</td> <td>Top Head</td> </tr> <tr> <td>d.</td> <td>Discharge Head</td> <td>20-40 Meter</td> </tr> <tr> <td>e.</td> <td>Discharge Pipe Dia</td> <td>50-75 mm</td> </tr> <tr> <td>f.</td> <td>Power Output</td> <td>To be mentioned</td> </tr> <tr> <td>g.</td> <td>Start Method</td> <td>Direct</td> </tr> <tr> <td>h.</td> <td>Suction Position</td> <td>Bottom Side Through Strainer</td> </tr> <tr> <td>i.</td> <td>Rated Current</td> <td>7-10 A</td> </tr> <tr> <td>j.</td> <td>Insulation Class</td> <td>F</td> </tr> <tr> <td>k.</td> <td>Volt</td> <td>440 V</td> </tr> <tr> <td>l.</td> <td>Frequency</td> <td>50-60 Hz</td> </tr> <tr> <td>m.</td> <td>Phase</td> <td>3</td> </tr> <tr> <td>n.</td> <td>Motor Power Input</td> <td>To be mentioned</td> </tr> </table>	a.	Capacity	35-45 Ton per hour	b.	Speed	2700-3500 RPM	c.	Discharge Position	Top Head	d.	Discharge Head	20-40 Meter	e.	Discharge Pipe Dia	50-75 mm	f.	Power Output	To be mentioned	g.	Start Method	Direct	h.	Suction Position	Bottom Side Through Strainer	i.	Rated Current	7-10 A	j.	Insulation Class	F	k.	Volt	440 V	l.	Frequency	50-60 Hz	m.	Phase	3	n.	Motor Power Input	To be mentioned
a.	Capacity	35-45 Ton per hour																																										
b.	Speed	2700-3500 RPM																																										
c.	Discharge Position	Top Head																																										
d.	Discharge Head	20-40 Meter																																										
e.	Discharge Pipe Dia	50-75 mm																																										
f.	Power Output	To be mentioned																																										
g.	Start Method	Direct																																										
h.	Suction Position	Bottom Side Through Strainer																																										
i.	Rated Current	7-10 A																																										
j.	Insulation Class	F																																										
k.	Volt	440 V																																										
l.	Frequency	50-60 Hz																																										
m.	Phase	3																																										
n.	Motor Power Input	To be mentioned																																										
8.	Country of Origin	Italy, USA, UK																																										
9.	Country of Manufacture	Italy, USA, UK																																										
10.	Year of Manufacture	2022 and/or later																																										
11.	Source of Supply	To be mentioned																																										
12.	Port of shipment	-																																										
13.	Manufacturer's Name and Address	Italy, USA, UK																																										
14.	Supplier/ Local Agent	-																																										
15.	Certificate and Document of Authentication	-																																										
16.	Packing	-																																										
17.	Warranty	01 Year on the date of BN acceptance																																										
18.	Installation	-																																										
19.	Test, trial and acceptance	On board ship																																										
20.	Installation by supplier	-																																										
21.	Site visit (Focal Point)	-																																										
22.	Training	-																																										
23.	Accessories	Cable- 20 Mtr, Discharge Hose- 30 Mtr, Nozzle- 02 in no, Adaptor- 01 in no.																																										
24.	Picture	-																																										
25.	Weight	Not more than 30 Kg.																																										


 MAHFUZUR RAHMAN
 Commander BN
 Engineer Officer
 BNS SOMUDRA JOY